

The VP83 includes:

- 1 AA alkaline battery for 130 hours of battery life
- Integrated 3.5 mm gold-plated audio connector output cable for quick connection to camera or recording device
- Standard size shoe mount with a 1/4" threaded base for on-camera use or easy mounting on a stand
- Foam windscreen (Windjammer® available separately)

Features**Exceptional Audio Performance with User-Friendly Controls**

- High sensitivity and low self-noise with wide frequency range for natural audio reproduction
- Highly directional supercardioid / lobar polar pattern that rejects unwanted off-axis audio while clearly capturing the intended sound source
- Superior RF immunity that avoids unwanted audio artifacts from cellular and RF devices
- Easily accessible controls at the back of the microphone:
- Three-position gain (-10 dB pad, 0, +20 dB boost) to compensate for different recording environments
- Low-cut filter to eliminate background noise and room ambience

Durable and Lightweight

- Integrated Rycote® Lyre® shock mounting system that provides robust isolation from vibration and mechanical noise (exclusively developed with Rycote for the VP83)
- Durable, all-metal construction that meets legendary Shure quality standards in an ultra-lightweight design

Specifications:

Type:	Electret condenser
Frequency Response:	50–20,000 Hz
Polar Pattern:	Supercardioid / lobar